
	DECLARATION OF PERFORMANCE	
		Page 1 of 1
No 04.11		

1. Unique identification code of the product-type:

Total Proof PU Hybrid

Intended use:

Coating (C) for surface protection of concrete structures according to principles 1(PI), 2 (MC) and 8 (IR)

2. Manufacturer:

Druckfarben Hellas S.A. Megaridos Ave., Kallistiri area, GR-19300 Aspropyrgos, Greece

3. Systems of AVCP (Assessment and Verification of Constancy of Performance):

System 4 & System 3 for Reaction to Fire

4. Harmonised Standard: **EN 1504-2:2004**

Notified Bodies:

TECHNICKY A ZKUSEBNI USTAV STAVEBNI PRAHA s.p. (TZUS), NB 1020

5. Declared Performances:

Essential Characteristics	Performance
Reaction to fire	E
Permeability to CO ₂	S _D > 50 m
Permeability to Water Vapour	Class I
Capillary Absorption and permeability to water	$w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$
Adhesion strength by pull-off test	$\geq 1.5 \text{ N/mm}^2$
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by (legal representative):



Sokratis Vavatsikos

Chemist N.K.U.A. |

Regulatory & Specifications Compliance Manager

Aspropyrgos-GREECE, on 21/02/2024