
	<b>DECLARATION OF PERFORMANCE</b>	
		Page 1 of 1
<b>No 05.25</b>		

1. Unique identification code of the product-type:

**FixoTile Pro 5, C1**

Intended use:

**Normal setting cementitious adhesive for internal tiling**

2. Manufacturer:

**Druckfarben Hellas S.A. Megaridos Ave., Kallistiri area, GR-19300 Aspropyrgos, Greece**

3. Systems of AVCP (Assessment and Verification of Constancy of Performance):

**System 3 & System 4 for Reaction to Fire**

4. Harmonised Standard: **EN 12004:2007 + A1:2012**

Notified Bodies:

**EUROTEST - CONTROL, NB 2085**

5. Declared Performances:

Essential Characteristics	Performance
Reaction to fire	Class A1 <sub>fl</sub>
<b>Bond Strength as:</b>	
-Initial tensile adhesion strength	≥ 0.5 N/mm <sup>2</sup>
<b>Durability, for:</b>	
-Tensile adhesion strength after water immersion	≥ 0.5 N/mm <sup>2</sup>
-Tensile adhesion strength after heat ageing	NPD
-Tensile adhesion strength after freeze-thaw cycles	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by (legal representative):



**Sokratis Vavatsikos**

Chemist N.K.U.A.]

Regulatory & Specifications Compliance Manager

Aspropyrgos-GREECE, on 25/07/2024