

Go Interior



THINNING
0 - 10%



COVERAGE
10 - 12 m²/L



APPLICATION
brush or roller



DRYING
1 - 2 hours

Emulsion paint
for interior use

- » **High coverage**
- » **Effectively covers imperfections**
- » **Suitable for frequent repainting**

Cost-effective emulsion paint for interior walls and ceilings. It is suitable for frequent repainting, and it covers imperfections of the surface creating an even matt finish. It is easy to apply with a very good performance.

A/a (WB) Interior matt walls and ceilings (Gloss <25@60°).

- VOC Limit Value: 30g/L.
- Maximum VOC content of the ready to use product: 29 g/L.

TECHNICAL DATA

Density ISO 2811 @ 25°C	1.57 g/mL (±0.07) *
Solids Content w/w ISO 3251	65% (±3) *
Viscosity ASTM D 562-05 @ 25°C	110KU (±15)
Application Viscosity ASTM D 562-05 @ 25°C	85 KU (±15)
Gloss Level @ 60° ISO 2813	<3 GU
Gloss Level @ 85° ISO 2813	<13 GU
pH	8.5 - 9.5
Whiteness Index ASTM E 313-98	86.5 (±1.5) **
Yellowness Index ASTM E 313-98	1.0 (±0.5) **
Coverage per coat	10 - 12 m ² /L ***
Recommended dry film thickness (2 coats)	70 µm(±5)

* Depending on the shade and the tinting base.

** Only for white.

*** Depending on the shade, the application method and the surface absorption.

Go Interior

Emulsion paint
for interior use

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, solid, and free of dust, grease, residues, blistered paint, etc. Avoid dust generation and exposure to it.

- » **On new surfaces:** Before applying the topcoat, apply one coat of a water-based primer, such as KRAFT ECO DUR AQUA, KRAFT HAFT or KRAFT GO PRIMER.
- » **On surfaces that need repair:** Use KRAFT SPACHTEL or KRAFT PUTTY or the suitable KRAFT repairing material

APPLICATION INSTRUCTIONS

- » Before start painting, thin the paint up to 10% v/v with tap water and stir well.
- » You can apply with a brush or a roller.
- » The product should be tinted only with the KRAFT INSPIRED COLOR tinting system on the recommended tinting base.
- » For shade and finish consistency, it is advisable to use containers of the same batch number. In case of different batch numbers, it is recommended to have them mixed in a larger container.
- » KRAFT GO INTERIOR White can be tinted with the KRAFT MASTER BASICS basic colors for countless light shades.
- » Apply 2 coats of KRAFT GO INTERIOR for an ideal result.
- » Minimum recoating time: 3-4 hours.
- » Dry to touch: 1-2 hours at 25°C and 50% relative humidity. Drying time is subject to weather conditions.
- » Avoid patching after the completion of painting. A slight difference in absorbance or in the application method might cause color or gloss unevenness. If necessary, it is advisable to recoat the whole surface.
- » Do not apply at temperatures below 5°C or above 35°C and at a relative humidity of 65% or higher.

AFTER USE INSTRUCTIONS

- » Clean the tools immediately with warm water and soap.
- » Close the canister well to preserve it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight or frost conditions.

PACKAGING

Available in White, in 750ml, 3L and 9L containers, and in tinting base P in 1L, 3L and 9L containers.

HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for maximum 24 months from the date of production. Keep containers tightly closed when not in use.

06/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarbengroup.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr