

Nitro Solvent 2000



**Nitro solvent
for 2-components paints**

» **2-components paints
solvent**

High quality solvent for thinning 2-components epoxy or PU paints which are applied with a brush, a roller or a spray gun on wooden, metallic or construction surfaces. It enhances leveling, workability and drying of the paint during application. It is also suitable for removing grease from metals prior to paint application and for cleaning the painting tools after use.

» **Ideal for epoxy
and PU paints**

» **Suitable for cleaning
surfaces/tools**

ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ

Density ASTM D4052 @ 15 °C	0.85-0.87g/mL
Solubility in water	Insoluble

Nitro Solvent 2000

Nitro solvent
for 2-components paints

APPLICATION INSTRUCTIONS

- » The product is ready to use.
- » To be applied in an open or well-ventilated space only.
- » Wear protective gloves and use protective equipment for the face and the eyes.
- » Thin the 2-components paint up to the recommended percentage depending on the product.
- » Thin and stir the mix to a homogenous consistency.
- » Do not apply at temperatures below 5°C or above 35°C.

AFTER USE INSTRUCTIONS

- » Close the canister well to keep it in good condition for future use.
Store before or after opening in a cool place, avoiding sunlight or frost conditions.

PACKAGING

Available in 0.75L, 4L and 16L containers.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read label before use. For further information please consult the Safety Data sheet.

Poison Centre Telephone:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for a maximum of 24 months from the date of production. Keep containers tightly closed when not in use.

09/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr