

Putty™



THINNING
0%



COVERAGE
2-3 m²/Kg



APPLICATION
putty knife,
trowel



DRYING
3-4 hours

Elastomeric water-based putty
with microspheres

» Exceptionally flexible

» Doesn't crack

» Strong adhesion

Elastomeric water-based putty for repairing and waterproofing interior and exterior walls and terraces. It can be applied on concrete, bricks, cement, wood, plasters and plasterboards and it is suitable for filling cracks and joints. It contains special microspheres that ensure easy filling, minimum shrinkage upon drying, easy application and easy sanding. It features excellent adhesion on various materials and exceptional resistance to humidity, frost, alkalis and high mechanical stress.

A/g (W/B) Primers.

- VOC Limit Value: 30g/L.
- Maximum VOC concentration of the ready to use product: 29g/L.

TECHNICAL DATA

| | |
|--------------------------|------------------------------------|
| Density ISO 2811 @25°C | 1.21 g/mL (±0.05) |
| Viscosity ISO 2555 @25°C | 80.000m.Pas (±10.000) (sp.7/30rpm) |
| pH | 8.9 - 9.9 |
| Coverage per coat | 2 - 3 m ² /kg* |

* Depending on the roughness of the substrate .

Putty™

Elastomeric water-based putty
with microspheres

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean, and free of dust, grease, salts, rust, residues, blistered paint, etc.

- » **On new and/or porous substrates:** Prime with KRAFT ECO DUR AQUA diluted with 80% water.

APPLICATION INSTRUCTIONS

- » No thinning is required.
- » Stir well before and during application.
- » Apply with a putty knife, a trowel or a leveler to fill in cracks and dents of up to 1cm. For larger cracks use a suitable KRAFT sealant.
- » After complete drying it can be sanded with a suitable sandpaper.
- » After complete drying it can be recoated with any KRAFT water-based emulsion or enamel paint, after proper preparation.
- » Do not apply at temperatures below 5°C or above 35°C and at a relative humidity 65% or higher.
- » Dry to touch: 3-4 hours at 25°C and 50% relative humidity. Drying time is prolonged in high humidity and in cold temperatures.
- » Avoid inhalation of dust using a suitable protective respiratory equipment during sanding.

AFTER USE INSTRUCTIONS

- » Clean the tools and the product residues immediately with water and soap or detergent.
- » Close the canister well to preserve it in good condition for future use.
- » Store before or after opening in a cool place, avoiding sunlight or frost conditions.

PACKAGING

Available in 0.5Kg, 1Kg, 4Kg and 15Kg containers.

HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for maximum 24 months from the date of production. Keep containers tightly closed when not in use.

06/23 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr