

# Relief



**THINNING**  
0%



**COVERAGE**  
2 - 3m<sup>2</sup>/Kg



**APPLICATION**  
brush,  
relief roller



**DRYING**  
1 - 2 hours

Decorative textured coating

## » Easy application

White, water-based textured coating for interior and exterior use. It is suitable for walls, plaster, concrete, bricks, wood, chipboard, and asbestos cement. It is highly resistant to rain, frost and air pollution. It covers minor imperfections of the substrate.

**A/c (WB) Exterior walls of mineral substrate.**

- VOC Limit Value: 40g/L.
- Maximum VOC concentration of the ready to use product: 29g/L.

## » Excellent textured finish

## » Effective coverage

### TECHNICAL DATA

Density ISO 2811 @ 25°C	1.54 g/mL (±0.04)
Viscosity ASTM D 562-05 @ 25°C	130 KU (±10)
pH	8.8 - 9.5
Coverage per coat	2- 3 m <sup>2</sup> /Kg
Recommended dry film thickness (2 coats)	200µm (±20)

# Relief

Decorative textured coating

## SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean, and free of dust, grease, salts, rust, residues, blistered paint, etc.

- » **Putty application:** KRAFT PUTTY, scrub, KRAFT SPACHTEL, scrub, priming with KRAFT ECO DUR AQUA.
  - » **On new surfaces:**
    - **Exterior:** 1 coat of KRAFT ECO DUR AQUA or KRAFT DUR AQUA WHITE and 2 coats of KRAFT RELIEF. For better protection a final coat of KRAFT 4 SEASONS or KRAFT 4 SEASONS ELASTIC is recommended 2-3 days after application.
    - **Interior:** 1 coat of KRAFT ECO DUR AQUA or KRAFT DUR AQUA WHITE and 2 coats of KRAFT RELIEF. 1st coat thinning: 20%.
  - » **On surfaces with trapped moisture, mold, fungi and algae:** Removal of residues, KRAFT MOLD BLOCKER cleaning, priming with KRAFT ECO DUR AQUA and 2 coats of KRAFT RELIEF.
  - » **On surfaces with stains, smoke, trapped moisture:** 1 coat of KRAFT ECO STAIN BLOCKER AQUA and 2 coats of KRAFT RELIEF 24 hours later.
  - » **Fresh concrete, plaster, stucco:** To be painted no earlier than 30 days after application of KRAFT ECO DUR AQUA primer.
- Allow new surfaces of plaster or concrete to dry completely for at least 30 days before the paint application.

## APPLICATION INSTRUCTIONS

- » You can apply with a brush, or a relief roller (spongy).
- » No thinning is required.
- » Minimum recoating time: 24 hours.
- » Dry to touch: 1-2 hours.
- » Stir well before and during application.
- » Do not apply at temperatures below 10°C or above 35°C and at a relative humidity 65% or higher.

## AFTER USE INSTRUCTIONS

- » Clean the tools and the product residues immediately with warm water and soap or detergent.

## PACKAGING

Available in White in 5Kg and 15Kg containers. It can be tinted with KRAFT Master Basics.

## HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793 777

## STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for maximum 24 months from the date of production. Keep containers tightly closed when not in use.

