

# Remover



**THINNING**  
0%



**CONSUMPTION**  
250 - 500mL/m<sup>2</sup>



**APPLICATION**  
brush, scrapper  
or spatula

Paint  
stripper

### » High performance

### » Easy to use

### » Dichloromethane-free

High performance dichloromethane-free paint stripper for easy removal of old solvent-based or water-based paints and varnishes from any surface (walls, floors, wood, metal etc.). Its special formula helps the effective removal of even very thick films of 1 or 2 components (PU or epoxy).

#### ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ

Density ISO 2811	0.96 g/mL (±0.02)
Viscosity ξώδες ASTM D 562-05 @ 25°C	90 KU (±15)
Consumption per coat	250 - 500 mL/m <sup>2</sup>

# Remover

## Paint stripper

### APPLICATION INSTRUCTIONS

- » The product is ready to use.
- » To be applied in an open or well-ventilated space only.
- » Wear protective gloves and use protective equipment for the face and the eyes.
- » Apply a thick coat of KRAFT REMOVER with a brush over the painted surface.
- » Allow 5-10 minutes to act for removal of 1-component paints and 15-30 minutes for 2-components paints.
- » In case of very old or high-build paints, apply a second coat of KRAFT REMOVER.
- » When the paint to be removed gets swollen, use a scrapper or a spatula.
- » Sand the surface with sandpaper and remove residues.
- » Clean the surface with KRAFT BRUSH SOLVENT or pressure wash with water.
- » Do not apply at temperatures below 5°C or above 35°C.

### AFTER USE INSTRUCTIONS

- » Close the canister well to keep it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight or frost conditions.
- » Clean the tools immediately with water and soap.

### PACKAGING

Available in 0.375L and 0.75L containers.

### HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793777

### STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for a maximum of 24 months from the date of production. Keep containers tightly closed when not in use.

09/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

**DISCLAIMER:** The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.kraftpaints.com](http://www.kraftpaints.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

#### DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501  
[www.druckfarben.gr](http://www.druckfarben.gr) | [www.kraftpaints.gr](http://www.kraftpaints.gr)



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm  
e-mail: [paints.orders@druckfarben.gr](mailto:paints.orders@druckfarben.gr)