



KRAFT
PAINTS
DRIVEN BY INNOVATION

DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

Safety Data Sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CK202650001
KRAFT BETONYL White

AUC1-T0PG-R00D-WV1U

1.2. Relevant identified uses of the substance or mixture and uses advised against

Solvent-borne Acrylic Cement Paint

1.3. Details of the supplier of the safety data sheet

DRUCKFARBEN HELLAS SA
MEGARIDOS AVENUE
19300 ASPROPYRGOS
GREECE

(ATTIKI)

Tel. +30 210 5519500
Fax +30 210 5519501

psafety@druckfarben.gr

1.4. Emergency telephone number

0030-210-7793777

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.2. Label elements





DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 2. Hazards identification

H304
H317
H336
H412
EUH066

P210
P331
P280
P301+P310
P370+P378
P501

P102

Contains:

2.3. Other hazards

SECTION 3. Composition/information on ingredients

3.2. Mixtures

x = Conc. %

Classification (EC) 1272/2008 (CLP)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

INDEX 649-327-00-6

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 919-857-5

CAS 64742-48-9

REACH Reg. 01-2119463258-33

TITANIUM DIOXIDE

INDEX

EC 236-675-5

CAS 13463-67-7

REACH Reg. 01-2119489379-17-0000

01-2119489379-17-0197 01-2119489379-17

Naphtha (petroleum), hydrotreated heavy

INDEX 649-327-00-6

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066

EC 265-150-3

CAS 64742-48-9

REACH Reg. 01-2119463258-

Zinc Oxide

INDEX 030-013-00-7

Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 215-222-5

CAS 1314-13-2

REACH Reg. 01-2119463881-32-0073 01-2119463881-32

Xylene

INDEX 601-022-00-9

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 3. Composition/information on ingredients

Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine

INDEX

Skin Sens. 1A H317

EC 605-296-0

CAS 162627-17-0

REACH Reg. 01-2119970640-38-0000

1-Methoxy-2-Propanol

INDEX 603-064-00-3

Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-539-1

CAS 107-98-2

REACH Reg. 01-2119457435-35

ETHYLBENZENE

INDEX 601-023-00-4

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

EC 202-849-4

CAS 100-41-4

LC50 Inhalation vapours: 17,2 mg/l/4h

Acetone

INDEX 606-001-00-8

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 200-662-2

CAS 67-64-1

REACH Reg. 01-2119471330-49-0003

Quartz (Crystalline Silica)

INDEX

Substance with a community workplace exposure limit.

EC 238-878-4

CAS 14808-60-7

SECTION 4. First aid measures

4.1. Description of first aid measures

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5. Firefighting measures

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections

SECTION 7. Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

SECTION 8. Exposure controls/personal protection

8.1. Control parameters



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 8. Exposure controls/personal protection

Xylene

Threshold Limit Value

Zinc Oxide

Threshold Limit Value

Quartz (Crystalline Silica)

Threshold Limit Value

Acetone

Threshold Limit Value

1-Methoxy-2-Propanol

Threshold Limit Value



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 8. Exposure controls/personal protection

TITANIUM DIOXIDE

Threshold Limit Value

ETHYLBENZENE

Threshold Limit Value

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Health - Derived no-effect level - DNEL / DMEL

8.2. Exposure controls



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 8. Exposure controls/personal protection

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
------------	-------	-------------

9.2. Other information

SECTION 10. Stability and reactivity

10.1. Reactivity



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 10. Stability and reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



KRAFT
PAINTS
DRIVEN BY INNOVATION

DRUCKFARBEN HELLAS SA
KRAFT BETONYL White

SECTION 11. Toxicological information



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 11. Toxicological information

11.2. Information on other hazards

SECTION 12. Ecological information

12.1. Toxicity

12.2. Persistence and degradability



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 12. Ecological information

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Endocrine disrupting properties

12.7. Other adverse effects

SECTION 13. Disposal considerations

13.1. Waste treatment methods



KRAFT
PAINTS
DRIVEN BY INNOVATION

DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 14. Transport information

14.1. UN number or ID number

14.2. UN proper shipping name

14.3. Transport hazard class(es)



14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



DRUCKFARBEN HELLAS SA

KRAFT BETONYL White

SECTION 15. Regulatory information

15.2. Chemical safety assessment

SECTION 16. Other information

- Flam. Liq. 2
- Flam. Liq. 3
- Acute Tox. 4
- Asp. Tox. 1
- STOT RE 2
- Eye Irrit. 2
- Skin Irrit. 2
- STOT SE 3
- Skin Sens. 1A
- Aquatic Acute 1
- Aquatic Chronic 1
- Aquatic Chronic 3
- H225
- H226
- H312
- H332
- H304
- H373
- H319
- H315
- H335
- H317
- H336
- H400
- H410
- H412
- EUH066



KRAFT
PAINTS
DRIVEN BY INNOVATION

DRUCKFARBEN HELLAS SA
KRAFT BETONYL White

SECTION 16. Other information



KRAFT
PAINTS
DRIVEN BY INNOVATION

DRUCKFARBEN HELLAS SA
KRAFT BETONYL White

SECTION 16. Other information