

Wood Care™



THINNING
0%



COVERAGE
5 m²/L



APPLICATION
brush



DRY TO TOUCH
1-2 hours

Wood
preservative

» Effectively protects from woodworm

Colorless wood preservative, suitable for the preparation of exterior wooden surfaces prior to varnish application. It penetrates deeply into the pores of wooden surfaces such as exterior doors, frames, fences, pergolas, linings, outdoor furniture and effectively protects them from wood-decay fungi, blue stain fungi and insects like woodworm and termites. It is compliant with the new European Legislation.

It contains: Permethrin (ISO), Propiconazole and 3-iodo-2-propynyl butylcarbamate. It can cause allergic reaction.

Approved by the Ministry of Rural Development and Food. Product registration Number: ΤΠ8-0089.

» Penetrates deeply into the wood

» Prevents fungi and blue stains formation

TECHNICAL DATA

Density ISO 2811 @ 25°C	~ 0,8 g/mL @ 25 °C
Solids Content w/w ISO 3251	6-10%
Total Coverage	5 m ² /L*

Wood Care™

Wood preservative

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry and free of dust, mold, resins, residues, blistered paint, etc.

- » On new wooden surfaces: Remove grease and resins using KRAFT BRUSH SOLVENT, sand along the grain and remove dust with a wet lint-free cloth. Cure existing knots and apply 1-2 coats of KRAFT WOOD CARE for protection against woodworm and fungi. Then, apply 2-3 coats of KRAFT WOOD CLASS or KRAFT WOOD SHIELD impregnation varnish and/or 2 coats of KRAFT WOOD STYLE or KRAFT WOOD AQUA wood-stain varnish.
- » On painted wooden surfaces: Remove all residues of old paints or varnishes using KRAFT REMOVER, clean the surface with KRAFT BRUSH SOLVENT or sand well with a proper sandpaper. After the surface is completely dry and all residues have been removed, repair all damaged parts of the wood with a proper putty. Then, apply 2-3 coats of KRAFT WOOD CLASS or KRAFT WOOD SHIELD impregnation varnish and/or 2 coats of KRAFT WOOD STYLE or KRAFT WOOD AQUA wood-stain varnish.

APPLICATION INSTRUCTIONS

- » You can apply with a brush.
- » The product is ready to use.
- » Dry to touch: 1-2 hours at 23°C and 60% relative humidity.
- » Minimum recoating time: 24 hours.
- » Stir well before application.
- » Wood preservatives must be used with caution.
- » Do not apply on wooden surfaces which are in contact with the ground or water.
- » Do not apply at temperatures below 5°C or above 35°C and at a relative humidity 80% or higher.
- » Before application, check the moisture of the wooden surface. It should not exceed 18%.

AFTER USE INSTRUCTIONS

- » Close the canister well to preserve it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight.
- » Clean the tools immediately with KRAFT BRUSH SOLVENT.

PACKAGING

Available in 0.75L and 2.5L containers.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

KEEP AWAY FROM CHILDREN'S REACH.

Use biocides with caution.

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Tel:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C.

09/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
 e-mail: paints.orders@druckfarben.gr