

# Wood Style™



**THINNING**  
5-10%



**COVERAGE**  
12-14m<sup>2</sup>/L



**APPLICATION**  
brush



**DRY TO TOUCH**  
2-3 hours

Decorative wood varnish

## » High durability

Solvent-based polyurethane alkyd decorative varnish of high quality. It is suitable for all exterior and interior wooden surfaces. It features great clarity and great resistance against dirt pick-up. It is also painted and applied beautifully. Its elasticity helps to follow the contractions-expansions of wood, preventing cracking or flaking.

### A/e (SB) Interior/Exterior trim varnishes and woodstains including opaque woodstains

- VOC Limit Value: 400g/L
- Maximum VOC concentration of the ready to use product: 399g/L

## » Excellent finish

## » High elasticity and hardness

### TECHNICAL DATA

Binder Type	Alkyd /PU resins	
Density ISO 2811 @ 25°C	0,94 g/mL (±0,02)	
Solids Content w/w ISO 3251	62,5%(±2)*	
Viscosity ASTM D 562-05 @ 25°C	75KU (±15)*	
Gloss Level @ 60° ISO 2813	Gloss	>90GU
	Satin	70GU (±8)
Drying Time (Recorder) ASTM D-5895	1-3h	
Coverage per coat	12-14 m <sup>2</sup> /L**	

\* Depending on the finish

\*\* Depending on the application method and the surface absorption.

## Wood Style Aqua™

Water-based polyurethane decorative wood varnish

### SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, solid, and free of dust, residues, blistered paint, etc.

- » On new surfaces: Before applying the varnish, remove grease and resins using KRAFT BRUSH SOLVENT, wet sand parallel to the grain and remove dust with a wet lint-free cloth. Cure existing knots, apply 1 coat of KRAFT WOOD CARE for protection against woodworm, fungi, etc. In case you want a color effect on the wood, before applying the product apply 1-2 coats of KRAFT WOOD CLASS impregnation varnish.
- » On painted surfaces: Remove all residues of old paints or varnishes using KRAFT REMOVER, clean the surface with KRAFT BRUSH SOLVENT or sand well with a proper sandpaper. After the surface is completely dry and all residues have been removed, repair all damaged parts of the wood with a proper putty.

### APPLICATION INSTRUCTIONS

- » Before start painting, thin 5-10% v/v with KRAFT BRUSH SOLVENT and stir well.
- » The moisture of the wooden surface should not exceed 10%.
- » Do not apply on wooden surfaces which are in contact with the ground or water.
- » The durability of the material is reduced when applied on horizontal surfaces that suffer mechanical stress.
- » You can apply with a brush.
- » Apply 2 coats of KRAFT WOOD STYLE for an ideal result.
- » To be applied in an open or well-ventilated space.
- » Minimum recoating time: 24-48 hours.
- » Dry to touch: 2-3 hours at 25°C and 50% relative humidity. Drying time is subject to weather conditions.
- » Do not apply at temperatures below 10°C or above 35°C and at a relative humidity 60% or higher.

### AFTER USE INSTRUCTIONS

- » Close the canister well to keep it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight or frost conditions.
- » Clean the tools immediately with KRAFT BRUSH SOLVENT and then with warm water and soap.
- » Avoid exposure of the painted surface to rain for the following 7 days after application.
- » You can clean the painted surfaces gently with a soft sponge and water, or in case of stubborn stains, with a small amount of detergent, at least 15 days after painting.

### PACKAGING

Available in transparent gloss and satin finish, in 0.75L and 2.5L containers.

### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Tel:

+30 210 7793 777

### STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for a maximum of 24 months from the date of production. Keep containers tightly closed when not in use.

09/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

**DISCLAIMER:** The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website [www.kraftpaints.com](http://www.kraftpaints.com), as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

#### DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501  
[www.druckfarben.gr](http://www.druckfarben.gr) | [www.kraftpaints.com](http://www.kraftpaints.com)



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm  
 e-mail: [paints.orders@druckfarben.gr](mailto:paints.orders@druckfarben.gr)