

# Wood Style Aqua™



**THINNING**  
0 - 10%



**COVERAGE**  
10 - 12m<sup>2</sup>/L



**APPLICATION**  
brush



**DRY TO TOUCH**  
½-1 hour

Water-based polyurethane  
decorative wood varnish

### » High protection

Water-based polyurethane acrylic decorative varnish of high quality. It is suitable for all exterior and interior wooden surfaces. It features high resistance to weather conditions and to frequent washing. Its crystal transparency gives a distinctive look to the wood. It has a mild odor and is painted and applied beautifully. Its elasticity helps to follow the contractions-expansions of the wood, preventing cracking or flaking.

#### A/e (WB) Interior/Exterior trim varnishes and woodstains including opaque woodstains

- VOC Limit Value: 130g/L
- Maximum VOC concentration of the ready to use product: 129g/L

### » Crystal transparency

### » High elasticity and durability

#### TECHNICAL DATA

Binder Type	PU/Ac	
Density ISO 2811 @ 25°C	1,04 g/mL(±0,02)	
Solids Content w/w ISO 3251	34%(±3)	
Viscosity Flow Cup No4 @ 25°C ISO 2431	115 (±30) sec*	
pH	8,5-9,5	
Gloss Level @ 60° ISO 2813	Gloss	85 -95 GU
	Satin	35-50 GU
	Matt	15-25 GU
Coverage per coat	10-12 m <sup>2</sup> /L**	

\* Depending on the finish

\*\* Depending on the application method and the surface absorption.

# Wood Style Aqua™

Water-based polyurethane decorative wood varnish

## SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, solid, and free of dust, residues, blistered paint, etc.

- » **On new surfaces:** Before applying the varnish, remove grease and resins using KRAFT BRUSH SOLVENT, sand along the grain and remove dust with a wet lint-free cloth. Cure existing knots and apply 1 coat of **KRAFT WOOD CARE** or **KRAFT WOOD CARE AQUA** for protection against woodworm and fungi. In case a color effect on the wood is required, before applying the product apply 1-2 coats of **KRAFT WOOD SHIELD** impregnation varnish.
- » **On painted surfaces:** Remove all residues of old paints or varnishes using KRAFT REMOVER, clean the surface with KRAFT BRUSH SOLVENT or sand well with a proper sandpaper. After the surface is completely dry and all residues have been removed, repair all damaged parts of the wood with a proper putty.

## APPLICATION INSTRUCTIONS

- » Before start painting, thin up to 10% v/v with tap water and stir well.
- » The moisture of the wooden surface should not exceed 10%.
- » Do not apply on wooden surfaces which are in contact with the ground or water.
- » The durability of the material is reduced when applied on horizontal surfaces that suffer mechanical stress.
- » You can apply with a brush.
- » Apply 2 coats of KRAFT WOOD STYLE AQUA for an ideal result.
- » Minimum recoating time: 24 hours.
- » Dry to touch: 1/2-1 hour at 25°C and 50% relative humidity. Drying time is subject to weather conditions.
- » Do not apply at temperatures below 10°C or above 35°C and at a relative humidity 60% or higher.

## AFTER USE INSTRUCTIONS

- » Close the canister well to preserve it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight or frost conditions.
- » Clean the tools immediately with warm water and soap.
- » You can clean the painted surfaces gently with a soft sponge and water, or in case of stubborn stains, with a small amount of detergent, at least 15 days after painting.

## PACKAGING

Available in transparent gloss, satin and matt finish, in 0.75L and 2.5L containers.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Tel:

+30 210 7793 777

## STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for a maximum of 24 months from the date of production. Keep containers tightly closed when not in use.

09/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

**DISCLAIMER:** The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website [www.kraftpaints.com](http://www.kraftpaints.com), as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

### DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501  
[www.druckfarben.gr](http://www.druckfarben.gr) | [www.kraftpaints.com](http://www.kraftpaints.com)



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm  
 e-mail: [paints.orders@druckfarben.gr](mailto:paints.orders@druckfarben.gr)