

Yacht Care™



THINNING
0-5%



COVERAGE
14-16m²/L



APPLICATION
roller or airless
spray gun



DRY TO TOUCH
2-4 hours

Yacht
varnish

» High durability

Durable, protective and decorative polyurethane modified colorless varnish with strong UV filters. Suitable for all exterior wooden surfaces such as wooden boats, yachts, outdoor furniture, pergolas, frames, doors, windows, wales. It features exceptional durability thanks to its high concentration in UV filters and it prevents cracking and flaking. It forms an elastic, waterproof surface, protecting wood exposed to the sea (water and salt) and to intense sunlight, for long.

A/e (SB) Interior/Exterior trim varnishes and woodstains including opaque woodstains

- VOC Limit Value: 400g/L
- Maximum VOC concentration of the ready to use product: 399g/L

» Excellent waterproofing

» UV resistance

ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ

Binder Type	Alkyd/PU resins
Density ISO 2811 @ 25°C	0,92 g/mL(±0.02)
Solids Content w/w ISO 3251	61% (±3)
Viscosity ASTM D 562-05 @ 25°C	80 KU (±10)
Gloss Level @ 60° ISO 2813	>92,0GU
Drying Time (Recorder) ASTM D-5895	1-3 h
Coverage per coat	14-16 m ² /L*

* Depending on the application method and the surface absorption.

Yacht Care™

Yacht varnish

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, solid, and free of dust, mold, residues, blistered paint, etc. Sand with a proper sandpaper along the grain and smooth the surface well. Wet sanding is recommended to avoid dust generation and exposure to it.

- » **On new wooden surfaces:** Before applying the varnish, remove grease and resins using KRAFT BRUSH SOLVENT, sand along the grain and remove dust with a wet lint-free cloth. Apply 1 coat of **KRAFT WOOD CARE** for protection against woodworm and fungi.
- » **On old wooden surfaces:** Remove all residues of old paints or varnishes using KRAFT REMOVER and then clean the surface with a solvent.
- » **On painted surfaces:** Check the stability of the surface. If it is good enough, directly apply the varnish. If not, remove all residues of old paints or varnishes using KRAFT REMOVER, clean the surface with KRAFT BRUSH SOLVENT or sand well with a proper sandpaper. After the surface is completely dry and all residues have been removed, repair all damaged parts of the wood with a proper putty and then apply the varnish.

APPLICATION INSTRUCTIONS

- » Before start painting, thin 5% v/v with KRAFT BRUSH SOLVENT or KRAFT NITRO 1100 for application with an airless spray gun and stir well.
- » The moisture of the wooden surface should not exceed 10%.
- » Do not apply on wooden surfaces which are in contact with the ground or water.
- » The durability of the material is reduced when applied on horizontal surfaces that suffer mechanical stress.
- » You can apply with a brush, a roller or an airless spray gun.
- » Apply 2 coats of KRAFT YACHT CARE for an ideal result.
- » To be applied in an open or well-ventilated space.
- » Minimum recoating time: 24 hours.
- Dry to touch: 2-4 hours at 25°C and 50% relative humidity. Drying time is subject to weather conditions.
- Do not apply at temperatures below 5°C or above 35°C and at a relative humidity 60% or higher.

AFTER USE INSTRUCTIONS

- » Clean the tools immediately with KRAFT BRUSH SOLVENT and then with warm water and soap.
- » Close the canister well to preserve it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight or frost conditions.
- » Avoid exposure of the painted surface to rain for the following 5 days after application.

PACKAGING

Available in transparent, gloss finish, in 0.75L container.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Tel:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for a maximum of 24 months from the date of production. Keep containers tightly closed when not in use.

09/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
 e-mail: paints.orders@druckfarben.gr